

Oils & Lubricants

ACDelco**BE CERTAIN.**

INNOVATION STARTS WITH THE ORIGINAL



PART NO.

**19347201 / 19350981
19350980**

ACDELCO DEXOS2™ DIESEL FULLY SYNTHETIC

**Available in: SAE 5W-30
SAE 5W-40**

BENEFITS

Maximum engine life

Wider temperature range capability of the synthetic base fluid ensures correct oil viscosity to reduce friction at start-up, and to provide maximum lubricity during high temperature operation. The effective anti-wear additive system minimizes wear in even the most sophisticated valve train mechanisms, including those with variable valve timing.

Maximum power and performance

Metallic detergent and ashless dispersant additive system ensures maximum power and performance by providing superior control of ring belt and piston skirt deposits, even under the most severe operating conditions.

Reduce emission

Formulated with latest generation technology containing reduced levels of metals, phosphorus and sulfur, it maximizes the life of sensitive catalysts in catalytic converters and reduces the plugging rate of diesel particulate filters

PRODUCT FEATURES

Dexos 2™ is a fully synthetic diesel engine oil formulated for use in passenger car and light truck gasoline and diesel engines under all operating conditions. It is a low SAPS engine oil suitable for use in diesel powered vehicles with exhaust particulate filters / EGR systems and provides exceptional cleaning power, engine wear protection and improved fuel consumption.

PERFORMANCE STANDARDS

5W-30

- Dexos 2™
- Meets and Exceeds API CJ-4 Standards
- ACEA C2 / A5 / B5
- MB 229.51/229.31
- MB 226.5
- BMW LL-04
- VW 502 00 / 505 01

5W-40

- Dexos 2™
- Meets and Exceeds API CJ-4 Standards
- ACEA C3-12
- MB 229.51/229.31
- BMW LL-04
- PORSCHE A40

SDS

CLASSIFICATION: Not classified according to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) Fourth revised edition.

PHYSICAL AND CHEMICAL PROPERTIES:

Color: Varies depending on specification

Physical State: Liquid

Odor: Petroleum odor

pH: Not Applicable

Vapor Pressure: <0.01 mmHg (Estimated) @ 37.8 °C (100 °F)

Vapor Density (Air = 1): >1

Boiling Point: 315°C (599°F)

Solubility: Soluble in hydrocarbons; insoluble in water

Density: 0.85 kg/l @ 15°C (59°F) (Typical)

Viscosity: 9.5 mm²/s @ 100°C (212°F) Minimum

FLAMMABLE PROPERTIES:

Flashpoint: (Cleveland Open Cup) 200 °C (392 °F) Minimum

ENGINEERED FOR PERFORMANCE

