

# Oils & Lubricants



PART NO. 19347203

**ACDelco**

**BE CERTAIN.**

INNOVATION STARTS WITH THE ORIGINAL

**ACDelco**

**BE CERTAIN.**



**Available in:  
80W-90 & 85W-140**

## BENEFITS

- Excellent thermal durability and oxidation resistance
- Extreme pressure properties for extended gear life
- Superior protection against rust and corrosion
- Provide good foam inhibition

## APPLICATION:

- Recommended for use in spiral bevel and hypoid differentials, power dividers, and oil-lubricated steering axle wheel bearings

## PRODUCT FEATURES

ACDelco Select Gear Oil GL5 is an extreme pressure gear oil meeting API GL-5 formulated with selected high quality base oils and special "Extreme Pressure" additives. The engine can benefit from the highest pressure-absorption capacity as well as attrition and rust prevention.

## PERFORMANCE STANDARDS

- Meets the requirements of API Service categories GL-5 and GL-4

## SDS

**CLASSIFICATION:** Not classified as hazardous according to the Hazard Classification and Communication System of Hazardous Substances B.E. 2555 (2012)

### PHYSICAL AND CHEMICAL PROPERTIES:

**Color:** Amber

**Physical State:** Liquid

**Odor:** Petroleum odor

**pH:** Not Applicable

**Vapor Pressure:** <0.01 mmHg @ 37.8 °C (100 °F)

**Vapor Density (Air = 1):** >1

**Boiling Point:** 315°C (599°F)

**Solubility:** Soluble in hydrocarbons; insoluble in water

**Melting Point:** No data available

**Specific Gravity:** 0.8560 @ 15.6°C (60.1°F) (Typical)

**Viscosity:** 95 mm<sup>2</sup>/s @ 40°C (104°F) (Typical)

### FLAMMABLE PROPERTIES:

Flashpoint: (Cleveland Open Cup) 150 °C (302 °F) Minimum